



PIVOT PIN - FOR SPHERICAL PLAIN BEARING COTTER PIN OR SNAP RING TYPE

PENINSULAR[®] CYLINDER COMPANY

METRIC HIGH PRESSURE HYDRAULIC CYLINDER ACCESSORIES
SMALL BORE SERIES - ISO 6020-2
WORKING PRESSURE - 160 BAR (2320 PSI)
RATED PRESSURE - 250 BAR (3625 PSI)


ORDERING EXAMPLE:

PART # IHP12-72P = COTTER PIN TYPE PIVOT PIN
PART # IHP12-72PG = SNAP RING TYPE PIVOT PIN



DIMENSIONS IN MILLIMETERS

ORDER NUMBER	TYPICAL BORE DIAMETER	NOMINAL FORCE (N)	JK H6	ES (MIN)	ET (MAX)	WEIGHT (KG)
IHP12-72P	25	8 000	12.0	31.0	39.6	0.035
IHP12-72PG						
IHP16-72P	32	12 500	16.0	41.0	49.6	0.075
IHP16-72PG						
IHP20-72P	40	20 000	20.0	51.0	60.2	0.145
IHP20-72PG						
IHP25-72P	50	32 000	25.0	61.0	70.2	0.260
IHP25-72PG						
IHP30-72P	63	50 000	30.0	71.0	80.8	0.380
IHP30-72PG						
IHP40-72P	80	80 000	40.0	81.0	94.5	0.895
IHP40-72PG						
IHP50-72P	100	125 000	50.0	101.0	116.5	1.630
IHP50-72PG						
IHP60-72P	125	200 000	60.0	121.0	136.6	2.950
IHP60-72PG						
IHP80-72P	160	320 000	80.0	161.0	179.2	6.730
IHP80-72PG						
IHP100-72P	200	500 000	100.0	201.0	220.4	13.50
IHP100-72PG						



ACCESSORY MOUNTING DIMENSIONS CONFORM TO ISO 8133

ACCESSORIES ARE DESIGNED FOR, BUT NOT LIMITED TO, ISO 6020-2 HYDRAULIC CYLINDERS

