



PIVOT PIN - PLAIN COTTER PIN OR SNAP RING TYPE PENINSULAR[®] CYLINDER COMPANY

METRIC HIGH PRESSURE HYDRAULIC CYLINDER ACCESSORIES
SMALL BORE SERIES - ISO 6020-2
WORKING PRESSURE - 160 BAR (2320 PSI)
RATED PRESSURE - 250 BAR (3625 PSI)


ORDERING EXAMPLE:

PART # IHP10-66 = COTTER PIN TYPE PIVOT PIN
PART # IHP10-66G = SNAP RING TYPE PIVOT PIN



DIMENSIONS IN MILLIMETERS

ORDER NUMBER	TYPICAL BORE DIAMETER	NOMINAL FORCE (N)	EK F8	EL (MIN)	ET (MAX)	WEIGHT (KG)
IHP10-66	25	8 000	10.0	29.0	37.6	0.023
IHP10-66G						
IHP12-66	32	12 500	12.0	37.0	45.6	0.040
IHP12-66G						
IHP14-66	40	20 000	14.0	45.0	53.4	0.061
IHP14-66G						
IHP20-66	50 & 63	50 000	20.0	66.0	75.2	0.182
IHP20-66G						
IHP28-66	80	80 000	28.0	87.0	96.9	0.407
IHP28-66G						
IHP36-66	100	125 000	36.0	107.0	120.5	0.930
IHP36-66G						
IHP45-66	125	200 000	45.0	129.0	144.0	1.635
IHP45-66G						
IHP56-66	160	320 000	56.0	149.0	164.6	3.100
IHP56-66G						
IHP70-66	200	500 000	70.0	169.0	187.4	5.390
IHP70-66G						



ACCESSORY MOUNTING DIMENSIONS CONFORM TO ISO 8133

ACCESSORIES ARE DESIGNED FOR, BUT NOT LIMITED TO, ISO 6020-2 HYDRAULIC CYLINDERS